



GALÉO 200 by POSLIGNE®

New-Generation Vertical Integrated
EPOS System



A photograph of a Galéo 200 POS terminal in a bar setting. The terminal is a slimline vertical design with a large, tilted touchscreen display. It is positioned on a dark bar counter. In the background, there is a bar with various bottles and red bar stools. The lighting is warm and focused on the terminal.

GALÉO 200 by POSLIGNE®

Galéo 200 slimline vertical design with reduced energy consumption

AURES proudly reveals **Galéo 200**, the latest-generation system in its range of "all-in-one" vertical-concept EPOS terminals, characterised by its slimline design and up-to-the-minute specification.

Galéo 200 features the HSD Exclusive integrated utility, an AURES innovation, along with an **Intel Atom Pineview Dual-Core D525** processor. This fanless EPOS solution offers maximum computing power combined with optimised energy consumption, making it ideal for the tough conditions often encountered in the catering and hospitality environments.

The **HSD Exclusive** utility (*Hardware Status Display*) which equips **Galéo 200** provides a multi-lingual, real-time data transmission and display interface.

This platform allows users to check system status data - including processor temperature and other technical readings - which are displayed on the terminal's touch screen, on request and at any time.

The **HSD Exclusive** solution also allows the key data from an entire batch of terminals to be centralised, automatically sending information via e-mail (for instance, to a store chain's Information Systems Manager or Hotline) for as many units and locations as required.

Galéo 200 is fanless and features an Intel Atom Pineview Dual-Core D525 processor, boasting 90% more computing power than its predecessor - as well as being more energy efficient (consumption of 13 watts for the processor as opposed to 24 previously), thus offering a smaller carbon footprint.

The innovative slim design of the **Galéo 200** enables reduced footprints at the till but guarantees extreme stability. Thumbscrews on the front and rear faces provide easy, tool-free access to the mechanics enabling quick and effective till maintenance.

Its vertical lines makes it particularly suitable for use in bars and fast food outlets, as well as for takeaway sales.

Galéo 200 is available in two colours, pearl and graphite.

The Galéo 200 Pack is supplied with the TRP 100 II thermal receipt printer.



- + Intel Atom Pineview Dual-Core D525 processor provides a fanless EPOS solution – ideal for harsh environments
- + 90% more processing power
- + Reduced energy consumption and smaller carbon footprint
- + HSD Exclusive integrated Solution
- + Elegant vertical integrated POS system – space saving
- + Enhanced stability
- + Front-mounted USB port
- + Integrated customer display
- + All cabling inside base (no visible wires)
- + Optional Flash drive (SSD)



HSD EXCLUSIVE
by POS L I G N E[®]

Model

Processor	Intel Atom Pineview Dual-Core D525
Chipset	ICH 8M
Memory (RAM)	2GB up to 4GB (2 x DDR3 SO DIMM)
Graphics memory	Up to 256MB shared RAM (Intel GMA 3150)
Hard drive	1 x SATA HDD 2.5" on removable support
Touchscreen	15" / Resistive ELO Touch / Adjustable (-20° ~ 65°)
Resolution	1024 x 768
Power Supply	External (65W – 19V 4.74A)
Weight	11kg
Dimensions	290 x 200mm (base) – Height: ~ 420mm (screen in vertical position)
Compatible OS	POSReady, Windows XP Pro, WIN 2000/NT 4.0, Windows 7, Linux

GALÉO 200

Inputs / Outputs

- 4 x USB 2.0 ports (1 to be used on front face)
- 4 x RS 232 serial ports (2 self-powered)
- 1 x parallel port (1 x 25-pin D-sub connector)
- 1 x LAN 10/100/1000 (RJ 45)
- 1 x cash drawer output (12 / 19V)
- 1 x audio input/output
- 1 x additional video output (optional)
- 1 x mini PCIe slot

Options

- Badge and magnetic card reader (MCR)
- Dallas key reader
- Combined Dallas key and magnetic card reader
- Contactless badge reader (MIFARE)
- Biometric (fingerprint) and MCR reader
- Extended 2GB RAM SO DIMM
- Additional video output
- Flash drive (SSD)



TRP 100 II

thermal EPOS receipt printer

Available as a PACK with the **Galéo 200**, the **TRP 100 II** is a sturdy point-of-sale thermal receipt printer which offers excellent value for money. It takes 80mm diameter paper rolls, features automatic loading and provides quality printing (160mm/sec).

It is available with a native USB (type A) connection and a DB 25 Serial interface; WIFI, Ethernet and Parallel port interfaces are also available as an option.

The **TRP 100 II** is supplied with all its cables and available in 2 colours, pearl and graphite.

Model

Printing method	TRP 100 II Direct thermal
Printing speed	160mm/sec
Printing width	max 72mm / 512 dots
Resolution	180 DPI
Paper loading	Easy paper drop in
Paper Width	80mm in standard (38mm – 82.5mm)
Paper Thickness	0.06 – 0.09mm
Roll diameter	Max 83mm
Interfaces	USB (type A) native + Serial DB25 interfaces
Interfaces (optional)	Paralell, Ethernet and WIFI
Power supply	External 24V
Dimensions (L x D x H)	152 x 202 x 150mm
Weight	1.7 kg



AURES

MANUFACTURER OF REMARKABLY
DIFFERENT EPOS TERMINALS

AURES France
32, rue du Bois Chaland
91090 Lisses, France
+33 (0) 1 69 11 16 60
pos@aires.com

AURES UK
Unit 2 Sycamore Court
Warrington Road, Manor Park
Runcorn, Cheshire, UK, WA7 1RS
salesuk@aires.com

AURES Germany
Maisacherstr. 118
82256 Fürstenfeldbruck
Deutschland
+49 (0)8141-22715-0
salesde@aires.com

AURES USA
8599 Prairie Trail Drive, Unit A-300
Englewood, Colorado. 80112, USA
Office: +1 303-495-5643
Toll Free: +1 866-491-3753
salesusa@aires.com

www.aires.com



POS L I G N E®

