

# Z-POS Series

“Always right there in front of your payments and transactions”

- The industry's premier point of sale solution for retailers
- Product reliability & safety
- Easy to install and maintain POS systems
- Green IT of low energy consumption



**Fan Free, Tool Free Z-POS**  
The Best hit model Z-POS has the powerful features and smart design.



The Best hit model Z-POS has the powerful features and smart design. Z-POS is two-tone black and white, curved edges for a modern look and focuses on a user-friendly design. The first product in Korea adopts the frame Touch technology and 9.7-inch Dual Monitor option. The I/O (input/output) ports have been placed on the top of the panel, to aid ease of installation and hide cabling. Z-POS has adopted hand-screws to the MSR, HDD and Main Board to further increase ease of installation, servicing and user friendliness.



**User Friendly Design**  
Stylish All-in-one design with 9.7-inch dual monitor



**Easy to Service**  
I/O ports are placed on the top of the panel

**Z-1500**  
Normal Touch Type



**Z-9000**  
Frame Touch Type



## Z-POS Series, Stylish POS System

- No Fan, No Noise
- Product reliability & safety
- Easy to install and maintain with Fingertip screws
- Hidden Adapter and cables
- Waterproof and dust resistant LCD panel
- Green IT of low energy consumption



**Product reliability & safety**  
Proven product reliability and safety through EMC test, KCC, CE & FCC by Authorized Testing and Certification Bodies

**Green IT**

Intel Atom processor offers low power consumption. Low energy consumption can reduce unnecessary heat and expand the life span of POS components.



## Specification

Item	Specification	
<b>Main</b>	Formfactor	170 mm (W) x 170 mm (L) : Mini ITX Platform
	CPU	Onboard Intel Atom Processor Dual Core D2550 (1M Cache, 1.86 GHz)
	Chipset	Intel NM10 Express Chipset
	Memory	DDR3 SODIMM 2GB (up to 4GB by 2 x Slots)
	Storage	2.5" SATA 320GB HDD
<b>Primary Display</b>	LCD	15-inch TFT LED LCD, LVDS interface
	Resolution	1024 x 768
	Touch	15" 5-Wire Analog Resistive Touch (Serial I/F)
<b>Indicator</b>	2 x LEDs and 1 x Buzzer	
<b>Speaker</b>	1 x 1W	
<b>I/O Port</b>	USB	6 ports (2 x Side, 4 x Rear)
	Serial	4 RS-232C ports (3 x Powered DSUB-9, 1 x RJ-45) COM1/4 : 0/5/12V By Jumper, COM2/3 : 0/5/12V By BIOS Select
	PS/2	2 ports (1 x Mouse, 1 x Keyboard)
	LAN	2 Gigabit LAN ports
	VGA	1 VGA port
	Audio	2 ports (1 x Mic-in, 1 x Line-out)
<b>Power</b>	DC-IN	External 60W Adapter Input AC 100~240V/ 50~60Hz, Output DC 12V/5A
	<b>Dimension</b>	W x D x H mm 389 x 206 x 322
<b>Tilt Adjustment</b>	0°~50°	
<b>WEIGHT</b>	6.25kg / 7.47kg (with Dual Monitor)	
<b>User Environment</b>	Temperature	Operating -25 to 65
		Storage -35 to 75
<b>Optional Peripherals</b>	MSR	ISO 1,2,3 Tracks Reading
	OS	POSReady2009 / POSReady7
	Storage	SSD 32GB / 64GB / 128GB
	2nd Display	9.7-inch TFT LCD (1024 X 768) 9.7-inch TFT LCD (Touch Screen)

This specification can be changed without Prior notice

ver. ZPOS\_201307\_EA

**iClick IT and Epos Solutions Ltd.**  
215 Mill Street  
Brierley Hill  
DY5 2TJ

**TEL: 0121 288 3630**  
SUPPORT@ICLICKSOLUTIONS.CO.UK

